

 3333 SCOTT BLVD
 T: 1.408.227.4500

 SANTA CLARA, CA 95054
 FAX: 1.408.227.4550

WWW.ARUBANETWORKS.COM

CLIENT DEVICE INTEROPERABILITY TEST RESULTS

Document Version: v1.0				
Client Device Details				
Client Device Make			Honeywell	
Client Device Type			Mobile Device	
Client Device Model			EDA51	
Client Device OS type			Android 8.1.0	
Tested Client Device NIC capability			11ac, 1 Spatial Stream	
Test Configuration				
Aruba OS Version		8.9.0.0 – 81161		
Access Point		AP-535, AP-515		
Basic Wi-Fi Interoperability Test and Capability Results				
Feature	Support	Capability Details		
Association				
Supported Encryption Opmodes	1	Open, Mac Auth, Open WEP, PSK(TKIP/AES), Enterprise (TKIP/AES), Mixed (PSK/AES)		
Channels				
2.4 GHz Radio	1	1,6,11		
5 GHz Radio	1	36-165		
	Roaming			
Opportunistic Key Caching (OKC)	1	OKC is supported		
Fast Transition (802.11r)	✓ -	FT with both PSK and Enterprise SSID		
Protocols				
BSS Transition (802.11v)	1	BSS Transition Capable		
WMM Client (802.11e)	1	802.11e Capable		
WMM-PS (U-APSD)	X	Not Capable of UAPSD Power Save		
Radio Resource Management (802.11k)	1	802.11k Capable		
Management Frame Protection (802.11w)	1	Only MFP-Capable and not MFP-Required		
802.11h and 802.11d	1	Supports DFS and TPC		

NOTE: Client Device may support a superset of the above capabilities

ABBREVIATIONS: NR: Neighbor Report; BR: Beacon Report; LM: Link Measurement, TSM: Transmit Stream Measurement, MFP: Management Frame Protection, FT: Fast Transition, OKC: Opportunistic Key Caching, DFS: Dynamic Frequency Selection, TPC: Transmit Power Control, DL: Downlink, UL: Uplink, TWT: Target Wake Time, OFDMA: Orthogonal Frequency Division Multiple Access