

## CLIENT DEVICE INTEROPERABILITY TEST RESULTS

| Document Version: v1.0                                   |                         |   |
|--|-------------------------|---|
| Client Device Details                                    |                         |   |
| <b>Client Device Make</b>                                | <b>Samsung</b>          |   |
| <b>Client Device Type</b>                                | <b>Mobile Device</b>    |   |
| Client Device Model                                      | Samsung Galaxy S20 Plus |   |
| Client Device OS type                                    | Android 10              |   |
| Tested Client Device NIC capability                      | 11ax, 2 spatial stream  |   |
| Test Configuration                                       |                         |   |
| Aruba OS Version   | 8.7.0.0-75915           |   |
| Access Point   | AP515, AP535            |   |
| Basic Wi-Fi Interoperability Test and Capability Results |                         |   |
| Feature  | Support                 | Capability Details  |
| Association  |                         |   |
| Supported Encryption Opmodes                             | ✓                       | Open, Mac Auth, Open WEP, PSK(TKIP/AES), Enterprise (TKIP/AES), Mixed (PSK/AES) |
| Channels   |                         |   |
| 2.4 GHz Radio  | ✓                       | 2.41 ... 2.48 GHz; depending on the country approvals (channels 1-13)           |
| 5 GHz Radio  | ✓                       | 4.9 ... 5.8 GHz; depending on the country approvals (Channels 36-165)           |
| Roaming  |                         |   |
| Opportunistic Key Caching (OKC)                          | ✓                       | OKC Capable   |
| Fast Transition (802.11r)                                | ✓                       | FT with both PSK and Enterprise SSID  |
| Protocols  |                         |   |
| BSS Transition (802.11v)                                 | ✓                       | Supports BSS Transition   |
| WMM Client ( 802.11e)                                    | ✓                       | 802.11e Capable   |
| WMM-PS (U-APSD)  | X                       | Client Does not support U-APSD Power Save                                       |
| Radio Resource Management (802.11k)                      | ✓                       | 802.11k Capable   |
| Management Frame Protection (802.11w)                    | ✓                       | MFP-Capable and MFP-Required  |
| 802.11h and 802.11d                                      | ✓                       | DFS and TPC capable   |
| WPA3 Capabilities  |                         |   |
| OWE  | ✓                       | OWE Capable   |
| WPA3-SAE   | ✓                       | SAE Capable   |
| WPA3-CCM-128   | ✓                       | WPA3-CCM-128 Capable  |
| WPA3-SuiteB  | X                       | Not supported by client   |

|                  |   |                         |
|------------------|---|-------------------------|
| WPA3-AES-GCM-256 | X | Not supported by client |
|------------------|---|-------------------------|

| Roaming with WPA3             |   |  |
|-------------------------------|---|--|
| SAE+11r                       | X | Not supported by client                            |
| WPA3-CCM-128 + 11r            | ✓ | Capable of WPA3-CCM-128 + 11r                      |
| Suite-B +11r                  | X | Not supported by client                            |
| WPA3-AES-GCM256 + 11r         | X | Not supported by client                            |
| 802.11ax Client Capabilities  |   |  |
| 802.11ax Capable              | ✓ | 11ax Capable                                       |
| DL-OFDMA                      | ✓ | Capable of receiving OFDMA frames                  |
| UL-OFDMA                      | ✓ | Capable of transmitting OFDMA frames               |
| DL MU-MIMO                    | ✓ | Capable of receiving HE MU-MIMO frames             |
| UL MU-MIMO                    | X | Client cannot transmit HE MU-MIMO frames           |
| TWT Capable                   | ✓ | Individual TWT supported                           |
| 1024 QAM Capable              | ✓ | All rates up to MCS 11 supported in both Tx and Rx |
| Notes and Additional Comments |   |  |
|                               |   |  |

**NOTE:** Client Device may support a superset of the above capabilities

**ABBREVIATIONS:** NR: Neighbor Report; BR: Beacon Report; LM: Link Measurement, TSM: Transmit Stream Measurement, MFP: Management Frame Protection, FT: Fast Transition, OKC: Opportunistic Key Caching, DFS: Dynamic Frequency Selection, TPC: Transmit Power Control, DL: Downlink, UL: Uplink, TWT: Target Wake Time, OFDMA: Orthogonal Frequency Division Multiple Access