

CLIENT DEVICE INTEROPERABILITY TEST RESULTS

| Device Details | | |
|--|----------------------------|--|
| Client Device | iPhone SE | |
| Client Device Model | A1662 (MLY12LL/A) | |
| Client Device OS type | iOS 11.0 | |
| Tested Client Device NIC capability | 11ac,1ss (Spatial Streams) | |
| Test Configuration | | |
| Aruba OS Version | 6.5.x.x | |
| Access Point | AP-325 | |
| Basic Wi-Fi Interoperability Test and Capability Results | | |
| Feature | Support | Capability Details |
| Association | | |
| Supported Encryption Opmodes | ✓ | Open, Mac Auth, WEP (Static), PSK(TKIP/AES), Enterprise(TKIP/AES), Mixed (PSK/AES) |
| Channels | | |
| 2.4 GHz Radio | ✓ | 1,6,11 |
| 5 GHz Radio | ✓ | 36-165 |
| Roaming | | |
| Opportunistic Key Caching (OKC) | X | |
| Fast Transition | ✓ | Capable of FT |
| Protocols | | |
| BSS Transition (802.11v) | ✓ | BSS Transition Management exchange supported |
| Fast Transition (802.11r) | ✓ | FT supported with both PSK and Enterprise SSID |
| Radio Resource Management (802.11k) | ✓ | NR supported |
| Management Frame Protection (802.11w) | ✓ | MFP supported with both PSK and Enterprise SSID |

NOTE: Client Device may support a superset of the above capabilities

ABBREVIATIONS: NR: Neighbor Report; BR: Beacon Report; LM: Link Measurement, TSM: Transmit Stream Measurement, MFP: Management Frame Protection, FT: Fast Transition, OKC: Opportunistic Key Caching